



MATERIAŁ: № 1.2344
DIN X40CrMoV51

MATERIAL: № 1.2344
DIN X40CrMoV51

OBRÓBKA ŁBA: Hartowany i wyżarzany
HEAT TREATMENT: Hardened and annealed

TWARDOŚĆ: 42-46 HRc
HARDNESS: 42-46 HRc

d1	d2	M	T	K				
3,0	8	M-4	7	12				
3,5								
4								
4,5								
5	10	M-5	9	14				
5,5								
6								
6,5								
7								
7,5								
8	13,8	M-6	10	16				
8,5								
9								
9,5								
10								
10,5								
11								
11,5								
12	17	M-8	14	22				
12,5								
13								
13,5								
14								
14,5								
15	20,8	M-8	14	22				
15,5								
16								
16,5								
17								
18								
19	27	M-8	14	22				
20								
26					33	M-8	14	22
26								

DŁUGOŚĆ: 100, 150, 200, 250, 300, 350, 400, 450, 500, 550, 600
LENGTHS: 100, 150, 200, 250, 300, 350, 400, 450, 500, 550, 600

PRZYKŁAD ZAMAWIANIA: Rdzeń CZ: d1=4,5 mm L=150 mm
ORDER EXAMPLE: Core pin CZ: d1=4,5 mm L=150 mm

Nr. katalogowy: CZ-045150
Order number: CZ-045150